



Color: ■ gray

- Quick and easy to install
- Maintenance free connections to BS5733-MF for inaccessible areas
- Adjustable cable tie
- Screwless design
- Complies with BS EN 60670-22, BS 7671 and configurable to BS 5733-MF – Further information: Please, download the product detail data sheet.

Electrical data

Ratings per IEC/EN – Notes	
Ratings (note)	Rated current: up to 24 A; Rated voltage: 400 V; Rated impulse voltage: 4 kV

Physical data

Width	39 mm / 1.535 inches
Height	29 mm / 1.142 inches
Depth	95 mm / 3.74 inches

Mechanical data

Protection type	IP2X
-----------------	------

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0 MJ
Weight	28.4 g



Commercial data		
ETIM 8.0		EC001170
ETIM 7.0		EC001170
PU (SPU)		1 pcs
GTIN		4055143116404

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 207-3303

↓

Documentation			
Additional Information			
Technical Section	pdf	2246.92 KB	↓
207-3303 WAGO Box	pdf	610.86 KB	↓