

Toggle with Gripper

Wire Rope crimped with end stopper & toggle

Function:
Recommended for the suspension of HVAC, electrical and mechanical services.

Applications:
Suitable for profile roof cladding, light fittings, luminaries and other cavities.

Technical Data:

- SMACNA compliance- all products carry a 5:1 safety factor
- As per UL 1598, CSA C22.2 No.250.0-08
- Tested & Certified by TUV Nord.

Material Specification:	
Toggle	MS White Zinc
End Stopper	Ms Zn Trivalent
Wire rope	MS Zn Trivalent IS228, (ASTM-D117) -2016 IS-6745-2011
Max Load	280kg
SWL	56kg
Safety Factor	5:1



Code	Size	Price Each
ICWST3	7 x 7 Strand 2mm (3 metres)	
ICWST5	7 x 7 Strand 2mm (5 metres)	

Stud with Gripper

Wire Rope crimped with M8 stud

Function:
Recommended for the suspension of HVAC, electrical and mechanical services. (For indoor & stationary setting).

Applications:
Concrete ceilings, metal decking and pressed metal brackets (with nuts).


Technical Data:

- SMACNA compliance- all products carry a 5:1 safety factor
- Tested & Certified by TUV Nord.
- As per UL 1598, CSA C22.2 No.250.0-08

Material Specification:	
Stud	MS-En1A White Zinc
Wire rope	MS Galvanized IS228, (ASTM-D117) -2016, IS-6745-2011
Max Load	280kg
SWL	56kg
Safety Factor	5:1

Comes complete with drop-in anchor.

Also compatible with Wedge Nuts and Channel Nuts



Code	Size	Price Each
ICWSS3	7 x 7 Strand 2mm (3 metres)	
ICWSS5	7 x 7 Strand 2mm (5 metres)	

Loop Wire with Gripper

Wire Rope crimped with pre-formed loop.


Function:
Recommended for the suspension of HVAC, electrical and mechanical services.

Applications:
Purlins, beams, roof trusses and other accessible building features.

Technical Data:

- SMACNA compliance- all products carry a 5:1 safety factor
- As per UL 1598, CSA C22.2 No.250.0-08
- Tested & Certified by TUV Nord.

Material Specification:	
Ferrule	MS-En8D White Zinc (Hexagonal Crimped)
Wire rope	MS Galvanised IS228, (ASTM-D117)-2016, IS-6745-2011
Max Load	280kg
SWL	56kg
Safety Factor	5:1



Code	Size	Price Each
ICWSL3	7 x 7 Strand 2mm (3 metres)	
ICWSL5	7 x 7 Strand 2mm (5 metres)	

Snap Hook 'Y' with Gripper

Wire Rope crimped Snap Hooks.


Function:
Recommended for the suspension of HVAC, electrical and mechanical services.

Applications:
Suitable for use on cable trays etc.

Technical Data:

- SMANCA compliance - all products carry a 5:1 Safety Factor
- As per UL 1598, CSA C22.2 No.250.0-08
- Tested & Certified by TUV Nord.

Material Specification:	
Hook	MS-En8D White Zinc
Wire Rope	MS Galvanised IS228, (ASTM-D117)-2016, IS-6745-2011
Crimping	Hexagonal
Max Load	280kg
SWL	56kg
Safety Factor	5:1



Code	Size	Price Each
ICWSY3	7 x 7 Strand 2mm (3 metres)	
ICWSY5	7 x 7 Strand 2mm (5 metres)	

Wire Suspension Systems

Wide range of Wire & Accessories

- Cost Effective and Time Saving Solution over Threaded Rod
- Versatile Range to suit multiple applications including HVAC, Electrical , Engineering & more!
- Our Wire Suspension Systems are tested & certified by TUV Nord



Can't find what you're looking for?

For more information on our products please use our website!
www.deligo.co.uk



Industrial Accessories | Catenary Wire & Accessories

Stainless Steel Catenary Wire Kit 30 Metres

Code	Type	Price Each
ICWSSKIT	30 Metre Stainless Steel Catenary Wire Kit	

Includes:
1 of each ICWSS30, ICWSS5, ICWSSR and ICWSSH
10 of each ICWSS2 & ICWSSG
Material: Stainless Steel A2 (304)



Stainless Steel Individual Accessories

Code	Type	Price Each
ICWSSE	Eyelet for Catenary Wire	
ICWSSG	Wire Rope Grip	
ICWSSH	Hook Plate for Catenary Wire	
ICWSSR	Ring Plate for Catenary Wire	
ICWSSS	4" Strainer (Tensioner)	



Stainless Steel Catenary Wire

Code	Type	Price Each
ICWSS30	30 Metre Stainless Steel Catenary Wire	
ICWSS50	50 Metre Stainless Steel Catenary Wire	
ICWSS100	100 Metre Stainless Steel Catenary Wire	

Our range of Catenary Wire & Accessories, excluding the Carabiner Hook (ICWC), now in Stainless Steel.
Material: Stainless Steel A2 (304)



Wire Hanger ZY

Code	Size	Length (b)	Price 100
IWH660	M6 x 60	60mm	

Material: Steel
Usage: Medium duty installation, expansion type
Application: Suspended ceilings, catenary / suspension wire
Substrate Applicable: Concrete, stone and solid brickwork

Catenary Wire Kit 30 Metres

Code	Type	Price Each
ICWKIT	30 Metre Kit & Accessories	

Includes:
1 of each ICW30, ICWS, ICWR and ICWH
10 of each ICWE & ICWG



Individual Accessories

Code	Type	Price Each
ICWC	Carabiner Hook	
ICWE	Eyelet for Catenary Wire	
ICWG	Wire Rope Grip	
ICWH	Hook Plate for Catenary Wire	
ICWR	Ring Plate for Catenary Wire	
ICWS	4" Strainer (Tensioner)	



Catenary Wire Steel 2mm & 3mm

Code	Size	Price Each
ICW230	2mm x 30m Coil	
ICW250	2mm x 50m Coil	
ICW2100	2mm x 100m Drum	
ICW30	3mm x 30m Coil	
ICW50	3mm x 50m Coil	
ICW100	3mm x 100m Drum	

Material: Steel
Finish: Galv
Strand: 7



Scan here to be taken to our website (www.deligo.co.uk)



Industrial Accessories | Wire Suspension Systems

Why choose HangTyte?

HangTyte™ products are durable, cost-effective and are a more versatile alternative to other leading brands.

	HangTyte™	Zip Rize	Gripper 1 (Standard)	Gripper 2 (Standard)
Quick to Install	✓	✓	X	✓
Key/Toolless Operation	✓	✓	X	✓
TUV Nord Certified	✓	✓	✓	✓
SWL (Base on 2mm Wire)	56kg	50kg	45kg	45kg

Gripper



Cable Blocker/Gripper

Function:
Recommended for the suspension of HVAC, electrical and mechanical services (For indoor & stationary setting).


Applications:
Suitable for locking wire rope to insure desired safe working loads.

Technical Data:
• SMANCA compliance - all products carry a 5:1 Safety Factor
• As per UL 1598, CSA C22.2 No.250.0-08
• Tested & Certified by TUV Nord.

Material Specification:
Housing Type ZA2 Zinc
Locking Mechanism Ball Bearing
Release Mechanism Inbuilt release key
Spring Stainless Steel
Additional Safety Lock Brass
Max Load 565kg
SWL 113kg
Safety Factor 5:1



ICWL2
ICWL3



Code	Size	Price Each
ICWL2	1.5mm - 2.0mm	
ICWL3	2.4mm - 3.2mm	


Looped Anchor with Gripper

Wire Rope crimped masonry anchor.


Function:
Recommended for suspension of HVAC, Electrical and Mechanical services (For indoor setting)

Applications:
Concrete ceilings and cracked concrete ceilings
Technical Data:
• SMACNA compliance- all products carry a 5:1 safety factor
• As per UL 1598, CSA C22.2 No.250.0-08
• Tested & Certified by TUV Nord.

Material Specification:
MS-En1A with White Zinc
Max Load 280kg
SWL 56kg
Safety Factor 5:1



ICWSA3
ICWSA5



Code	Size	Price Each
ICWSA3	7 x 7 Strand 2mm (3 metres)	
ICWSA5	7 x 7 Strand 2mm (5 metres)	


Snaphook with Gripper

Wire Rope crimped with snaphook.


Function:
Recommended for the suspension of HVAC, electrical and mechanical services.

Applications:
Suitable for use on cable trays etc.
Technical Data:
• SMACNA compliance- all products carry a 5:1 safety factor
• As per UL 1598, CSA C22.2 No.250.0-08
• Tested & Certified by TUV Nord.

Material Specification:
Hook MS-En8D White Zinc
Wire rope MS Galvanized IS228, (ASTM-D117)
-2016, IS-6745-2011 Hexagonal
Max Load 280kg
SWL 56kg
Safety Factor 5:1



ICWSH3
ICWSH5



Code	Size	Price Each
ICWSH3	7 x 7 Strand 2mm (3 metres)	
ICWSH5	7 x 7 Strand 2mm (5 metres)	