


LOOX5 24V LEADS - COB, MONOCHROME, 8 MM

Loox driver to light connecting leads and light to light interconnecting leads for Loox5 COB flexible strip light LED 3069 shown on page 5.134A. Use of these leads provide IP20 degree of protection.

Loox5 IP20 24 driver to light lead, LED COB strip light monochromatic, 8 mm



- > Current carrying capacity: Max 5 A
- > Width: Silicone plug 10 mm
- > Supplied with: 1x lead plug/clip
- > For drill hole Ø 8 mm plug
- > Plastic
- > Order qty: 1 pc


5 24 V

IP20



Cable length	Cat. No.
100 mm	833.75.762
500 mm	833.75.763
2000 mm	833.75.764

Loox5 IP20 24 interconnecting lead, LED COB strip light monochromatic, 8 mm



- > Current carrying capacity: Max 5 A
- > Width: Silicone plug 10 mm
- > Supplied with: 1x lead plug/clip
- > For drill hole Ø 12 mm plug
- > Plastic
- > Order qty: 1 pc


5 24 V

IP20



Cable length	Cat. No.
50 mm	833.75.765
2000 mm	833.75.766

Loox5 IP20 Clip connector, LED COB strip light monochromatic, 8 mm



- > Current carrying capacity: Max 5 A
- > Width: Silicone plug 10 mm
- > Supplied with: 1x lead plug/clip
- > For drill hole Ø 12 mm plug
- > Plastic
- > Order qty: 1 pc

5 24 V

IP20



Length	Cat. No.
27.3 mm	833.75.767

TCH DESIGN 2020. © Häfele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice.

5

Lighting: Loox5 LED