

50952

## Vigor LED Microwave Emergency

### FEATURES

- 5 years (2 years + 3 years) extended warranty
- Gloss white & opal PC finish
- Constructed from polycarbonate
- Complete with built in microwave sensor
- 3 hours emergency maintained fitting
- Suitable for indoor or outdoor use
- Can be ceiling and wall mounted

### SPEC DATA

Product Wattage:	16W & 2W(EM)
Product Lumen:	1200
Lumen/W:	75
Kelvin:	4000
Energy Rating:	A+
Dimmable:	No
Beam Angle:	120°
Power Factor:	0.9
CRI:	80
Lifetime (Hours):	35000
LED Brand:	Epistar
SDCM:	<6
Driver Type:	Constant Current 380mA
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp:	-20 to 45 Degree
IP Rating:	65
IK Rating:	08
Product Weight (KG):	1.575
Terminal Block:	4-way fast fix
Class:	1

### MICROWAVE MOVEMENT SENSOR DATA

Operating Voltage:	220 ~ 240Vac
Hertz:	50/60
Rated Load:	400W (Capacitive load) 800W (Resistive load)
Stand-by Power:	≤ 0.5W
Sensitivity:	Ceiling Height 3m: 100% / 75% / 50% / 25% / 10% Ceiling Height 6m: 100% / 75% / 50% Wall Height 2m: 100% / 75% / 50% / 25% / 10%
Hold-time:	5s / 30s / 90s / 3min / 20min / 30min
Daylight Sensor:	2Lux / 10Lux / 25Lux / 50Lux / Disable
Microwave Frequency:	5.8 GHz ±75MHz
Transmitting Power:	1mW Max.
Detection Range:	Ceiling Height 3m: 3-6m (radius) Wall Height 1.5-2m: 12-15m
Detection Angle:	360° (Ceiling) / 120° (Wall)
Working Temperature:	-20°C ~ 60°C

