

Garage Unit IP40 Surface Mounted



Design Features

- Fully enclosed metal construction body with drop down metal lid.
- Circular cable entry knock-outs (20&25mm) on the top and bottom.
- Large and accessible wiring space, with extra space for RCBOs, MCBs.
- Flexible connection allows for various configurations of protected ways.
- Fitted with 20/40kA T2 DP Surge Protective Device (SP140 1P+N/1).
- Fitted with DP 100A main Switch.
- Fitted with Type A RCBO with Switched Neutral Line.
- Modern style finished in white polyester powder coating to RAL9010.
- Surface mounted.
- IP40.
- BSEN61439-3.

Part No	Description	W (mm)	H (mm)	D (mm)	Box Qty
---------	-------------	--------	--------	--------	---------

MMGU05-SR	5Way Mini Garage Unit, 100A Main Switch, 20/40kA DP Surge Protective Device, 40A Type A RCBO	143	200	89	12
-----------	--	-----	-----	----	----

4Way IP65 Metal Surge Protection Mini Garage Unit



Design Features

- Weatherproof metal IP65 enclosure offering circuit protection for electric vehicle chargers.
- Fully enclosed metal construction body with drop down metal cover and metal lid.
- 20mm diameter Circular cable entry knock-outs on the side top and bottom.
- Modern style finished in white polyester powder coating to RAL9010.
- Large and accessible wiring space Robust die cast construction.
- Fully enclosed metal construction body with drop down metal cover and metal lid.
- Complies with BS EN 61439-3, BS EN60947-3 & BS EN 61643-11.
- Raised Din rail improves cable routing.
- Weatherproof to IP65.
- SPD Type:T2.
- Colour : White, Gray & Black.
- Large and accessible wiring space.
- Robust die cast construction.

Part No	Description	W (mm)	H (mm)	D (mm)	Box Qty
AGU0465	IP65 4 Way Enclosure white	140	220	98.8	8
AGU0465/B	IP65 4 Way Enclosure Black	140	220	98.8	8
AGU0465/G	IP65 4 Way Enclosure Grey	140	220	98.8	8
AGU4-SP	IP65 4 Way Metal Enclosure c/w 100A Main Switch and 20/40kA DP Surge Protective Device (SA240)	140	220	98.8	8
AGU4-SR/W	IP65 4Way White Metal Enclosure c/w 100A Main Switch and 20/40kA DP Surge Protective Device (SP140 1P+N/1) ,40A Type A RCBO(AMR140B-030)	140	220	98.8	8
AGU4-SR/B	IP65 4Way Black Metal Enclosure c/w 100A Main Switch and 20/40kA DP Surge Protective Device (SP140 1P+N/1) ,40A Type A RCBO(AMR140B-030)	140	220	98.8	8
AGU4-SR/G	IP65 4Way Grey Metal Enclosure c/w 100A Main Switch and 20/40kA DP Surge Protective Device (SP140 1P+N/1) ,40A Type A RCBO(AMR140B-030)	140	220	98.8	8
AGU4-SNR	IP65 4Way White Metal Enclosure c/w 40A Type A RCBO(RNA40C-030) and 20/40kA 1P+N Surge Protective Device(SA140 1P+N)	140	220	98.8	8
AGU4-SNR/B	IP65 4Way Black Metal Enclosure c/w 40A Type A RCBO(RNA40C-030) and 20/40kA 1P+N Surge Protective Device(SA140 1P+N)	140	220	98.8	8
AGU4-SNR/G	IP65 4Way Grey Metal Enclosure c/w 40A Type A RCBO(RNA40C-030) and 20/40kA 1P+N Surge Protective Device(SA140 1P+N)	140	220	98.8	8
AGU63616	IP65 white 4 Way C/W 63A 30mA RCD+B6A & B16A MCB	140	220	98.8	8
AGU63620	IP65 white 4 Way C/W 63A 30mA RCD+B6A & B20A MCB	140	220	98.8	8
AGU63632	IP65 white 4 Way C/W 63A 30mA RCD+B6A & B32A MCB	140	220	98.8	8