

6181Y

Single Core PVC Insulated and PVC Sheathed Cable

DONCASTER CABLES

Manufactured to BS 6004 Table 3

Annealed Copper Conductor / PVC Insulated / PVC Sheathed. 300/500V

Conductor: Plain Annealed Copper Class 1 or 2 to BS EN 60228

Insulation: PVC Type TI1 to BS EN 50363-3

Sheating: PVC Type 6 to BS7655-4.2

Current Ratings: For current ratings refer to table 4D1 of BS7671 IET

Wiring Regulations

Designed for use in light industrial and domestic wiring. These cables are particularly suited for installation as meter tails and are intended for fixed installation in dry or damp premises.

These cables can be installed in conduit, in cable trunking and in cable ducting, or where there is deemed little risk of mechanical damage these cables can be clipped direct, on cable tray, embedded or in free air. These cables are not intended to be laid underground.

STANDARD CORE COLOURS









The British Cable Company You Can Trust













Single Core PVC Insulated and PVC Sheathed Cable

DONCASTER CABLES



Product Code	Harmonisation Code	Nominal Cross Sectional Area of Conductor (mm²)	Nominal stranding of conductor (mm)	Nominal radial thickness of insulation (mm)	Nominal Radial Thickness of sheath (mm)	Overall Diameter Lower Limit (mm)	Overall Diameter Upper Limit (mm)	Approximate Weight (kg/ km)
6181Y1.0	National Type	1.0	1 / 1.13	0.6	0.8	3.8	4.5	26
6181Y1.5	National Type	1.5	1 / 1.38	0.7	0.8	4.2	4.9	35
6181Y2.5	National Type	2.5	1 / 1.78	0.8	0.8	4.8	5.8	55
6181Y4.0	National Type	4.0	7 / 0.85	0.8	0.9	5.4	6.8	75
6181Y6.0	National Type	6.0	7 / 1.04	0.8	0.9	6.0	7.4	95
6181Y710	National Type	10.0	7 / 1.35	1.0	0.9	7.2	8.8	155
6181Y716	National Type	16.0	7 / 1.70	1.0	1.0	8.4	10.5	225
6181Y725	National Type	25.0	7 / 2.14	1.2	1.1	10.0	12.5	340
6181Y725F	National Type	25.0	19 / 1.28	1.2	1.1	10.0	12.5	340
6181Y735	National Type	35.0	7 / 2.52	1.2	1.1	11.0	13.5	445

Weight and dimensional information is provided as an approximate guide only.

