




EGN103



1 channel digital time switch weekly cycle

Technical characteristics

Main electrical features

| | |
|------------------------------|----------|
| Rated operational voltage Ue | 230 V AC |
| Nominal voltage | 230 V |
| Type of supply voltage | AC |

Dimensions

| | |
|-----------------------------|---------|
| Depth of installed product | 61.6 mm |
| Height of installed product | 90 mm |
| Width of installed product | 35.8 mm |

Power

| | |
|-------------------------------|---------|
| Power consumed | 0.39 VA |
| Power consumption (operation) | 350 mW |

Fluorescent bulbs control

| | |
|--|--------|
| Max. power with fluorescent parallel lamps | 400 W |
| Max. power fluo. duo lamp comp. series | 1000 W |

Incandescent bulbs control

| | |
|------------------------------------|--------|
| Max. power with incandescent lamps | 2300 W |
|------------------------------------|--------|

Installation, mounting

| | |
|-------------------|-------|
| Tightening torque | 1,2Nm |
|-------------------|-------|

Connection

| | |
|---|-------------------------|
| Connection cross-sect. flexible conductor | 1 / 6mm ² |
| Connection cross-sect. rigid cable | 1,5 / 10mm ² |
| Number of contacts | 1 |
| Type of contacts | 1 changeover |
| Type of connection | with screw terminal |

Settings

| | |
|-------------------------|------|
| Shortest switching time | 1 mn |
|-------------------------|------|

Equipment

| | |
|---------------------------------|---------|
| Type of programmable thermostat | Digital |
| Number of channels | 1 |
| Supply failure reserve | 5 years |

Use conditions

| | |
|------------------|---------------|
| Working accuracy | ± 1,5 s / 24H |
|------------------|---------------|