



EMN001



**IP20**

## Stair case time lag switch

### Technical characteristics

#### Configuration

Switch mode	NO contact
-------------	------------

#### Main electrical features

Rated operational voltage Ue	230 V
------------------------------	-------

#### Electric current

Acceptable current rating with AC1	16 A
------------------------------------	------

#### Dimensions

Depth of installed product	64 mm
----------------------------	-------

Width of installed product	17.5 mm
----------------------------	---------

#### Power

Max. power with fluo uncompensated lamps	3600 VA
--	---------

Power consumed	1 VA
----------------	------

Total power loss under IN	2 W
---------------------------	-----

Power dissipation per coil	0.25 W
----------------------------	--------

#### Power supply

Supply voltage	230 V
----------------	-------

#### Fluorescent bulbs control

Max. power with fluorescent parallel lamps	1000 VA
--	---------

#### Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

#### Installation, mounting

Mounting type	din-Rail
---------------	----------

#### Connection

Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
---	----------------------

Connection cross-sect. rigid cable	1,5 / 10mm <sup>2</sup>
------------------------------------	-------------------------

Connection type	3 and 4 wires
-----------------	---------------

Number of contacts	1
--------------------	---

Type of contacts	1NO
------------------	-----

Type of connection	with screw terminals
--------------------	----------------------

#### Settings

Time delayed range	30s / 10min
--------------------	-------------

#### Use conditions

---

Operating temperature

-10...55 °C