



EGN200

Multi-function time switch 2 channels bluetooth

Technical characteristics

| Main | electri | саі т | eatur | 25 |
|------|---------|-------|-------|----|

| Rated operational voltage Ue Nominal voltage | 230 V 230 V |
|-----------------------------------------------|---------------------|
| Nominal voltage | 230 V |
| | |
| Type of supply voltage | AC |
| Voltage | |
| Operating voltage | 230 V AC |
| Dimensions | |
| Depth of installed product | 61.6 mm |
| Height of installed product | 90 mm |
| Width of installed product | 35.8 mm |
| Power | |
| Power consumed | 0.6 VA |
| Power consumption (operation) | 350 mW |
| Lighting control | |
| Brightness measurement range | 1 / 2000 Lux |
| Fluorescent bulbs control | |
| Max. power with fluorescent parallel lamps | 400 W |
| Max. power fluo. duo lamp comp. series | 1000 W |
| Incandescent bulbs control | |
| Max. power with incandescent lamps | 2300 W |
| Installation, mounting | |
| Tightening torque | 0.5Nm |
| Connection | |
| Connection cross-sect. flexible conductor | 0.2 / 2.5mm² |
| Connection cross-sect. rigid cable | 0,2 / 4mm² |
| Number of contacts | 2 |
| Type of contacts | 1 changeover |
| Type of connection | with screw terminal |
| Settings | |
| Shortest switching time | 1 mn |

Equipment

| Type of programmable thermostat | Digital |
|---------------------------------|----------|
| Number of channels | 2 |
| Supply failure reserve | 10 years |
| Use conditions | |
| Operating temperature | -545 °C |
| Working accuracy | 60 |