

CLDLWIB 11

Clear Deep Lid Surface Sealed Box



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	Polycarbonate, Thermo-resistant ABS
Material sealing gasket	EPDM
Protection class	IP65
Temp. range min	-25 °C
Temp. range max	85 °C
Temperatures during install.	-5°C - 60°C
Glow wire test	650 °C
Impact resistance	IK07, IK08
External dimensions LxWxH	190x140x140mm
Type	CLDLWIB 11
UK-Number	50106964
Product Color	RAL 7035
WISKA-Order no.	50106964
Packing unit	1
Tariff number	85366990

Description:

Surface enclosure
1/4 turn fast screw system
Tamper-proof seal

Additional Info:

Double Insulation

Recommended accessories

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

27.11.2024

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice