

SPECIFICATION



Dunham II Tri Colour

3CCT LED Floodlight



Beam Angle
See Table



Input
220-240V



Life Hours
25,000



Dimmable
No



Colour Temperature
3000K 4000K 6000K



Black Casi ng Withou t PIR (IP6 5)	DU2B-10T	DU2B-20T	DU2B-30T	DU2B-50T
Black Casi ng With PI R (IP65)	DU2B-10T P	DU2B-20T P	DU2B-30T P	DU2B-50T P
White Casi ng Withou t PIR (IP6 5)	DU2W-10T	DU2W-20T	DU2W-30T	DU2W-50T
White Casi ng With PI R (IP65)	DU2W-10T P	DU2W-20T P	DU2W-30T P	DU2W-50T P
Max Powe r	10W	20W	30W	50W
Max Lume ns	1000	2000	3300	5500
Beam Angl e	110°	110°	110°	110°
Dimension s (mm)	104 x 125 x 27	125 x 152 x 28	168 x 209 x 27	200 x 237 x 36
Dimension s (mm) wi th PIR	104 x 165 x 55	125 x 189 x 55	168 x 252 x 54	200 x 287 x 57

Key Features

- PIR with 4th WIRE for manual override or slave
- Selectable 3 Colour Temperatures
- White and Black casings available
- 2KV Surge protection on non PIR
- Angled bracket for easy installation
- Supplied with 1m cable
- 2 year warranty

CRI >80 **IP 65**

Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.