

Cable management

Conduit

Flexible Corrugated Conduit

FCP series corrugated conduit is a very economical solution for a variety of applications due to its high flexibility, compression strength and colour range.

Suitable for embedding into floors and walls, the FCP series is often used for cable assemblies, underfloor wiring and cable tidying.

Features:

- Available in polypropylene
- Temperature range from -40°C to +120°C
- LSZH (Low Smoke Zero Halogen), UL resistant
- One piece, quick fitting, easy release, re-usable adaptor c/w locknuts



IP54 rated	IP68 rated					IP68 rated		
Nylon Part No.	Polypropylene Part No.	Trade Size (mm)	Internal Dia. (mm)	External Dia. (mm)	Coil Size (M)	Adaptors	Pack Quantity	Colour
FCN16	FCP16	16.0	12.0	16.0	100	FCA-16PN-PK50	50	Black
FCN20	FCP20	20.0	17.0	20.0	100	FCA-20PN-PK50	50	Black
	FCP20W	20.0	17.0	20.0	100	FCA-20W-PK50	50	White
FCN25	FCP25	25.0	23.0	25.0	100	FCA-25PN-PK50	50	Black
–	FCP32	32.0	26.0	31.0	100	FCA-32PN-PK25	25	Black

Flexible Conduit Contractor Pack

IP54 rated	IP68 rated	IP68 rated	Dimensions in mm		Pack Contents
Nylon Part No.	Polypropylene Black Part No.	Polypropylene White Part No.	Internal Diameter	External Diameter	
FCN20-PK10	FCP20-PK10	FCP20-PK10 WHITE	17.0	20.0	10m + 10 adaptors + 10 locknuts
FCN25-PK10	FCP25-PK10	FCP25-PK10 WHITE	23.0	25.0	10m + 10 adaptors + 10 locknuts
–	FCP32-PK10	–	26.0	31.0	10m + 10 adaptors + 10 locknuts



To keep up to date with **new products** and **special offers** go online at www.swaonline.co.uk

